

DEC 07 2007

Application No.: 10/731,530

Docket No.: JCLA10474

AMENDMENT

In The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claim 1. (currently amended) A manufacturing method of a cover layer of optical storage media, comprising the following steps:

- (a) providing a substrate;
- (b) forming a reflective layer on the substrate;
- (c) providing a plate having a ~~generally~~ flat surface;
- (d) applying a radiation-setting resin on the reflective layer;
- (e) compressing the radiation-setting resin with the plate to form a light-cure resin layer;
- (f) rotating the resulting structure to form a radiation-setting resin layer;
- (g) hardening the radiation-setting resin layer to form a hardened radiation-setting resin layer which serves as the cover layer; and
- (h) separating the plate from the hardened radiation-setting resin layer, wherein the hardened radiation-setting resin layer remains adhered to the substrate.

Claim 2. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein a material of the plate comprises plastic, glass or metal.

Application No.: 10/731,530

Docket No.: JCLA10474

Claim 3. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein a material of the radiation-setting resin comprises epoxy, acrylic resin or polyester.

Claim 4. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 1, further comprising repeating the steps (d) to (h) after the step (h).

Claim 5. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 1, wherein an average thickness of the cover layer is in a range of about 60 nm to about 150 nm.

Claim 6. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the method used in the step (h) to separate the plate from the substrate comprises a center hole blowing film stripping method.

Claim 7. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 1, further comprising a step of forming an adhesive layer on the substrate before the step (d).

Application No.: 10/731,530

Docket No.: JCLA10474

Claim 8. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the substrate comprises a blue laser optical information storage media.

Claim 9. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the blue laser optical information storage media comprises an optical information storage media, wherein the recording and replaying operations for a gallium nitride ("GaN") laser or an ultraviolet ("UV") laser disc system uses an NA greater than 0.5 of an object lens.

Claim 10. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the wavelength used by the GaN laser or the UV laser disc system is smaller than 460 nm.

Claim 11. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the substrate is a disc having a recording layer.

Claim 12. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the substrate is a disc having a plurality of recording layers.

Application No.: 10/731,530

Docket No.: JCLA10474

Claim 13. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the substrate is a disc having a digital signal structure.

Claim 14. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the substrate is a disc having a read-only structure.

Claim 15. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the substrate is a disc having a write-once structure.

Claim 16. (original) The manufacturing method of a cover layer of optical storage media of claim 1, wherein the substrate is a disc having a re-writable structure.

Claim 17. (currently amended) A manufacturing method of a cover layer of optical storage media, comprising the following steps:

- (a) providing a substrate;
- (b) forming a reflective layer on the substrate;
- (c) providing a plate having an adhesive layer with a generally flat surface formed thereon;
- (d) applying a radiation-setting resin on the reflective layer;
- (e) compressing the radiation-setting resin with the plate to form a light-cure resin layer;
- (f) rotating the resulting structure to form a radiation-setting resin layer of uniform thickness;

Application No.: 10/731,530

Docket No.: JCLA10474

(g) hardening the radiation-setting resin layer to form a hardened radiation-setting resin layer which serves as the cover layer; and

(h) separating the plate from the hardened radiation-setting resin layer, wherein the hardened radiation-setting resin layer remains adhered to the substrate.

Claim 18. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 17, wherein the adhesive layer comprises gold, silver, aluminum, chromium, platinum, nickel, copper palladium, silicon or alloy thereof.

Claim 19. (previously presented) The manufacturing method of a cover layer of optical storage media of claim 18, wherein the adhesive layer further comprises an organic material.

Claim 20. (original) The manufacturing method of a cover layer of optical storage media of claim 19, wherein the organic material comprises epoxy resin, acrylic resin, polyester, nitrocellulose, polyvinyl resin, polymethyl methacrylate (PMMA), fluoropolymers or silicone rubber.